

Application
for
United States Patent

To all whom it may concern:

Be it known that we, Robert A. Gentala, John DiDomenico, and Craig S. Rendahl,
have invented certain new and useful improvements in

***OPTICAL PATH STRUCTURE FOR OPEN PATH EMISSIONS SENSING
WITH SPINNING FILTER WHEEL***

of which the following is a full, clear and exact description:

**OPTICAL PATH STRUCTURE FOR OPEN PATH EMISSIONS SENSING
WITH SPINNING FILTER WHEEL**

PRIORITY

[0001] The present application is a continuation-in-part of pending U.S. patent application no. 09/934,272, filed August 21, 2001, entitled Optical Path Structure for Open Emissions Sensing, the disclosure of which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

[0002] The present invention relates generally to remote sensing systems. More particularly, the present invention relates to an apparatus for transmitting, reflecting, and detecting light in an open path sensing system such as a vehicle emission sensing system, having use in detecting and/or measuring one or more components of the air through which the light passes.

BACKGROUND OF THE INVENTION

[0003] Current methods of determining whether a vehicle is compliant with emission standards include open path and closed path emissions measurement systems. In a closed path system, an emission sensor is directly connected to the exhaust of the vehicle, such as by insertion into a tailpipe. An open path vehicular emissions measurement system collects data by a means other than a direct connection to the tailpipe, such as a remote sensor that analyzes the individual components of emissions. Open path vehicle emission systems are often preferable to closed path systems because they can be used in numerous locations and do not require the vehicle to stop for testing.

[0004] Various open path emission sensing systems have been known. One such device uses a radiation source on one side of a roadway that projects a beam across the roadway to be received by a detector. The radiation source and the detector are located on opposite sides of the roadway. The radiation source emits light spectra that may be used to detect an emission signature by way of absorption of light, or which alternatively may be used to excite emission components so as to cause the components to emit light. The detected emission signature can then be used in various applications, such as the measurement of a vehicle's compliance with emission limits and the determination of the type of fuel that a vehicle is using.

[0005] A disadvantage of many known arrangements is that the radiation sources and detectors must be placed on opposite sides of the roadway from each other. Since both the detectors and radiation sources require power to operate, this means that a separate power supply must be provided on each side of the roadway.

[0006] Some known arrangements have tried to overcome this problem by using a radiation source on one side of a roadway and a reflective apparatus located on the other side of the roadway.

[0007] Accordingly, it is desirable to provide an improved optical transmission, reflection, and detection system as herein disclosed.

SUMMARY OF THE INVENTION

[0008] It is therefore a feature and advantage of the present invention to provide an improved optical transmission, reflection and detection system. In accordance with one embodiment of the present invention, a gas component analysis system includes a first light source capable of emitting a first beam of light having known emission intensities corresponding to one or more of infrared, visible, and ultraviolet spectra. The system also includes a reflection unit, a detection unit capable of receiving the beam and measuring received intensities corresponding to the plurality of light spectra, and a processor capable of comparing the received intensities and identifying a concentration of a component corresponding to the intensities.

[0009] Preferably, the system also includes a first reflector positioned to receive the beam from the first light source and reflect the beam toward the reflection unit. The reflection unit is positioned to receive the beam from the reflector and reflect the beam. Also preferably, a second reflector is positioned to direct the beam reflected by the reflection unit so that the beam may be received by the detection unit. Each reflector preferably comprises an off-axis paraboloidal mirror.

[0010] Also preferably, the system also includes a filter wheel positioned to spin about an axis and receive the beam from the first light source and pass the beam to the reflection unit in pulses. The filter wheel preferably includes a plurality of filters, each of which substantially limits the passage of light to a predetermined spectral wavelength or range of wavelengths.

[0011] Also preferably, the first beam of light travels along an optical path to the reflection unit. In this embodiment, the system also includes a second light source capable of emitting a second beam of light having known emission intensities corresponding to one or more of infrared, visible, and ultraviolet spectra, as well as a beam splitter/combiner positioned to direct the second beam of light along substantially the same optical path to the reflection unit.

[0012] In an alternate embodiment, the system also includes a spinning reflector positioned to spin about an axis and receive the beam from the reflection unit and direct infrared components of the beam to the detection unit in pulses.

[0013] In accordance with another embodiment, a method of measuring concentrations of one or more components of a gas includes the steps of: (1) emitting at least one beam of light having known emission intensities corresponding to a plurality of infrared, visible, and ultraviolet spectra through the gas; (2) using a reflection unit to reflect the beam; (3) using a detection unit to receive the beam; (4) measuring received intensities in the beam corresponding to the plurality of light spectra; and (5) identifying a concentration of at least one component of the gas corresponding to a ratio of the emission intensities and the received intensities.

[0014] Preferably, the method embodiment also includes, either before or after the reflecting step, filtering the beam and passing the beam to the reflection unit in pulses. It may also include, before the detecting step, directing infrared, visible and ultraviolet components of the beam to different detectors and/or spectrometers in the detection unit. Also preferably, in the method embodiment identifying step is performed by a processing

device that is programmed to perform the calculation of a component concentration using a formula corresponding to the Beer-Lambert law.

[0015] In another embodiment, the invention provides, an optical system for a gas component analysis. The system has a first emitter for emitting a first light beam having a first spectrum; a second emitter for emitting a second light beam at a second spectrum; a first receiver for receiving the first light beam; and a second receiver for receiving the second light beam. The first light beam travels along a first path in a first direction and the second light beam travels along a second path in a second direction and at least a portion of the first light path overlaps with at least a portion of the second light path to form an overlapping beam, and at the overlapping beam the first direction is opposite to the second direction.

[0016] In another aspect, the invention provides an optical system for a gas component analysis, that has a first emitter located on a first side of a vehicle path for emitting a first light beam having a first spectrum across the vehicle path, a first receiver for receiving the first light beam, and a spinning filter wheel that filters the beam from the first emitter before the beam crosses the vehicle path.

[0017] In another aspect, the invention provides an optical system for a gas component analysis has a first emitter located on a first side of a vehicle path for emitting a first light beam having a first spectrum across the vehicle path, a first receiver for receiving the first light beam, a plurality of filter elements, and a spinning mirror face that reflects the beam so that the beam reaches each of the filter elements in sequence.

[0018] There have thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated.

There are, of course, additional features of the invention that will be described below and which will form the subject matter of the claims appended hereto.

[0019] In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein, as well as the abstract, are for the purpose of description and should not be regarded as limiting.

[0020] As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] FIG. 1 illustrates a preferred embodiment of a source unit of the present invention including housing with window, light sources, filter wheel, beam splitter/combiner, and reflector.

[0022] FIG. 2 illustrates a preferred embodiment of a reflection unit of the present invention.

[0023] FIG. 3 illustrates a preferred embodiment of a detection unit of the present invention including housing with window, reflector, beam splitter/combiner, detector and spectrometers.

[0024] FIG. 4 illustrates an exemplary filter wheel that may be used in accordance with one embodiment of the present invention.

[0025] FIG. 5 illustrates an alternate embodiment of a detection unit of the present invention including housing with window, reflector, beam splitter/combiners, spectrometers, spinning reflector, monolithic ellipsoidal mirror, filter array with gas cells, focusing reflector, and a single infrared detector.

[0026] FIG. 6 illustrates several elements of an exemplary computer of a type suitable for carrying out certain functions of the present invention.

[0027] FIG. 7 illustrates a detection unit using multiple spectrometers and a single detector.

[0028] FIG. 8 illustrates the properties of an ellipsoidal reflector.

[0029] FIG. 9 is a conceptual diagram of some basic components of the present invention, including light source, reflection unit, detection unit, and processor.

[0030] FIG. 10 illustrates the addition of reflectors to the components of FIG. 9.

[0031] FIG. 11 illustrates the properties of a paraboloidal reflector.

[0032] FIG. 12 further illustrates the properties of a paraboloidal reflector.

[0033] FIG. 13 illustrates the addition of multiple light sources with beam splitter/combiners to the components of FIG. 10.

[0034] FIG. 14 illustrates a modification of the embodiment shown in FIG. 13 illustrating the arrangement of opposed sources.

DETAILED DESCRIPTION OF PREFERRED
EMBODIMENTS OF THE INVENTION

[0035] A preferred embodiment of the present invention provides an improved optical source, reflection, and detection system for gas component analysis. A preferred embodiment includes a light source unit, which preferably includes one or more of infrared, visible, and ultraviolet light sources; a reflection unit; and a light detection unit. Preferably, light sources and detectors are contained within a housing. The light is transmitted through a gas, such as air containing vehicle emissions, reflected, and detected for analysis and measurement of the amount of absorption that has occurred at known wavelengths of the light. The amount of absorption may be used to determine concentrations of gases corresponding to the specific wavelengths.

[0036] In a preferred embodiment of this invention, infrared, visible, and ultraviolet radiation is combined into one beam, directed across a path such as a road along which vehicles travel and generate exhaust, reflected back across the path, collected and concentrated, separated again, and received by one or more discrete detectors and/or spectrometers. In order to be able to separately analyze each range of wavelengths, the infrared light passes through a sequence of filters and/or gas cells either before or after traversing the path of light across the road. The filters are preferably narrow band pass filters

and the gas cells contain known concentrations of gases of interest, such that each filter or combination of filters and gas cells is specific to a gas of interest. In one embodiment, a spinning wheel holds the filters and passes each filter in front of the infrared light source in sequence, before the light traverses the road. In an alternate embodiment, the infrared light, after traversing the road, is distributed by a spinning reflector, such as a mirror, into a stationary array of filters and/or gas cells in sequence to an ellipsoidal mirror or an array of ellipsoidal mirrors that focus the light into a single detector. The visible and ultraviolet light is directed to one or more spectrometers that can analyze the desired wavelength ranges directly.

[0037] A portion of a preferred embodiment of the present inventive apparatus is illustrated in FIG. 1. FIG. 1 illustrates a possible light source component of the present invention. The light source component shown includes an infrared light source 10, a source of visible light 11, and an ultraviolet light source 12. The infrared light 14 emitted by the infrared source 10 passes through a filter wheel 16, more completely described in FIG. 4. Then it is reflected by a beam splitter/combiner 18, and follows an optical path 20 until it reaches a reflector 26 such as an off-axis paraboloidal mirror or spherical mirror. An off-axis paraboloidal mirror is preferred over a spherical mirror due to the aberrations in light that occur with spherical mirrors, however production economics may dictate the use of spherical mirrors. The reflector 26 reflects the infrared light along a path 22, through a protective window 25 in the housing 27, leading to a reflection unit illustrated in FIG. 2.

[0038] The reflector 26 and other optical components described in this embodiment are protected by a window 25 that allows the transmission of all of the wavelengths of interest. This window 25 is attached to the housing 27 of the entire source unit. Preferably, the light sources and detectors are included within a single housing. However, the light

sources and the light detectors may optionally be provided in more than one housing. Also preferably, the housings are sealed to prevent contaminants such as soot, road dust, and other road debris from damaging or coating the internal components and thus degrading the light signal received and/or transmitted by them. Also preferably, the sealed housings contain windows to allow light of the wavelengths of interest to leave and enter the housings as required for the light to travel along the desired optical path. These windows are preferably made of a material such as calcium fluoride (CaF_2), sapphire, or other material that will pass light of all wavelengths of interest with little or no attenuation. Optionally, the windows may be coated by a particular type of coating such as an anti-reflection coating or other suitable coating to enhance the transmission of light of the wavelengths of interest.

[0039] The infrared light source 10 may be any source that emits a sufficient intensity of light of the wavelengths of interest. The reflectors and optical path length determine the size of the spot from the infrared source that contributes to the light beam. Preferably the source is chosen, such that the light emitting area of the filament is as close to that spot size as possible for minimum power consumption.

[0040] Preferably, the filter wheel 16 is a spinning wheel that is powered by a motor 15 that spins the wheel 16 about an axis 19. Also preferably, a synchronization device 58 is provided to track the position and rotational speed of the filter wheel 16. Features of the filter wheel 16 are more completely illustrated in FIG. 4.

[0041] In addition, visible light from source 11 is focused by an optical element 13 to bring diverging light rays back into a focus through the center of ultraviolet source 12 where it is combined with the ultraviolet light from source 12 into a combined beam 24. The combined visible and ultraviolet light 24 passes through the beam splitter/combiner 18 such

that it also follows optical path 20 to the reflector 26, where the light is reflected to also follow path 22 out window 25 toward the reflection unit illustrated in FIG. 2. The visible light source 11 may be a light emitting diode (LED), which emits light in a narrow range of wavelengths, or another visible source such as a halogen lamp that emits a broader range of wavelengths. The advantage of passing the visible light through the ultraviolet light source is eliminating the need for another beam splitter/combiner, saving optical power that would otherwise be lost by the inefficiency of the beam splitter/combiner, in addition to saving space within the enclosure 27. However, if it is desirable to have an ultraviolet source 12 of a design that does not allow for pass-through of the visible light, then alternatively, the visible source 11, and ultraviolet source 12 may be reconfigured to take, for example, positions 146 and 144 as illustrated in an arrangement of sources in FIG. 13 that will be discussed further below.

[0042] The visible light source 11 is an option and is not required for gaseous measurements. However, such a source allows the performance of additional tests on detected light associated with visible spectra, such as an opacity test. One type of opacity test that may be performed is the Society of Automotive Engineers J1667 opacity test, also known as the "Snap Acceleration Test", which measures concentrations of light spectra in the range of 562 through 568 nanometers. Preferably, the visible source 11 can be sufficiently broad in its output wavelength characteristics to also permit detection of blue smoke, which may be indicative of a vehicle that is burning excessive lubricating oil, and particulate matter of varying sizes. Alternatively, more than one visible source optimized for specific causes of exhaust opacity may be used.

[0043] The ultraviolet light source 12 is preferably an ultraviolet lamp such as deuterium lamp, a xenon lamp, or another lamp that has ultraviolet light emission characteristics broad enough to include wavelengths of interest.

[0044] As FIG. 1 illustrates, where multiple light sources such as components 10, 11, and 12 are provided, the emitted beams preferably follow substantially the same optical path 20 toward the reflector 26. The reflector 26 is positioned such that light sources 10, 11, and 12 are near the focal point of the reflector 26 and the reflected light 22 is parallel to its axis of rotation. The angle between the incoming 20 and reflected light 22 and the focal length are determined by the design of the reflector 26 and may be chosen based on considerations of component layout and F-number. (F-number of an off-axis paraboloidal mirror is defined as the diameter of the mirror divided by its effective focal length.) Thus, light 20 transmitted to the reflector 26 is reflected in a direction 22 that is away from the original light sources 10, 11, and 12. In addition, if beam splitter/combiner 18 is a neutral density filter, it is preferably chosen so that the proportion of visible and ultraviolet light passed and the proportion of infrared light reflected are balanced according to the requirements of the detection unit. Optionally, a beam splitter/combiner 18 that is sensitive to different wavelengths such as a dichroic beam splitter may be used instead of a neutral density filter for beam splitter/combiner 18. In order to use some types of beam splitter/combiners, the positions of the infrared 10 and visible/ultraviolet sources 11, 12 may be reversed.

[0045] Optionally, only the infrared light source 10, and not the visible or ultraviolet sources 11, 12, may be provided. In such an embodiment, the beam splitter/combiner 18 may also optionally be omitted, with the infrared light source 10, filter wheel 16, and associated components, taking the position of the ultraviolet source 12 in such an alternative arrangement. This option of the preferred embodiment may be desired for more economical

utilizations of this embodiment where not all exhaust emissions constituents are desired to be measured, or a preference exists to simplify the production of such an embodiment with the potential compromise of poorer data quality.

[0046] FIG. 2 illustrates an exemplary reflection unit, which in an embodiment used to detect vehicle emissions is preferably placed across the road from the light source and detector components, creating an open-path emissions testing system. The reflection unit includes a retro-reflective system, preferably a vertical system, and preferably comprising three mirrors positioned to form 90° angles with respect to each other. A vertical orientation of the mirror assembly is preferred in order to adequately capture the emissions of vehicles of all profiles and heights. Referring to FIG. 2, incoming light 22 is reflected by a first mirror 30 and a second mirror 32. The first and second mirrors are adjacent or substantially adjacent to each other to form a 90° angle. The light reflected by the first and second mirrors is transmitted to a third mirror 34. As FIG. 2 illustrates, the flat reflective portion of third mirror 34 forms a 90° angle with the flat reflective portions of both first mirror 30 and second mirror 32. It is not important to have mirrors 30,32 on top of mirror 34, as this orientation could be reversed without any change to the quality of reflection of light. Light 36 that is reflected by third mirror 34 is then transmitted to the detection unit and travels in a direction that is parallel to the incoming light 22 in a configuration as illustrated in FIG. 9 to be discussed later in this text. The incoming light 22 and/or the reflected light 36 pass through an air component that is to be measured, such as vehicle emissions.

[0047] FIG. 3 illustrates an exemplary detection unit that receives the light that is generated by the source component of FIG. 1, and reflected by the reflection unit of FIG. 2. Referring to FIG. 3, incoming light 36 passes through a protective window 35 that has similar characteristics to the window of the source unit illustrated in FIG. 1, is reflected by a reflector

38 such as an off-axis paraboloidal mirror or spherical mirror that reflects light along an optical path 40 at an angle relative to the incoming light 36. The light transmitted along the optical path 40 is reflected by a beam splitter/combiner 44 that directs infrared light 48 toward infrared detector 50. Preferably, the infrared detector 50 is positioned within the focal volume so that the light will over-bathe the detector's active area to allow for system vibration without adversely affecting measurements by causing a portion of the detector's active surface to temporarily not have light exposure in a vibration occurrence. Focal volume is defined as the three-dimensional volume of light, in which the light is focused to its maximum intensity, in this instance infrared light 48, that travels to the detector 50. Maximum intensity of light occurs when all lights rays are concentrated into the smallest cross-sectional area of the focal volume. This cross-sectional area is not necessarily located at the focal point of the reflector 38, but is located farther away from the reflector 38 than the focal point.

[0048] Small, economical, durable, and versatile spectrometers 42, 43 are commercially available for most ranges of wavelengths of interest in the visible and ultraviolet regions. In the infrared region, however, spectrometers are less practical than individual detectors optimized for particular ranges of wavelengths. These infrared detectors are expensive and require cooling and complicated electronics for support. It is therefore a great advantage to use only a single infrared detector 50 in the detection unit. If separate detectors are used to detect the intensity of each wavelength or band of wavelengths of interest, the calibration problem caused by the different sensitivities of the different detectors must be addressed. This problem is further compounded because sensitivities change with time and temperature and can be different for each detector. Therefore a system using only a single infrared detector 50 is much simpler and is preferred.

[0049] The infrared detector 50 is preferably composed of mercury-cadmium-telluride (MCT), preferably utilizing at least three-stage thermal electric cooling. However, a lead-selenide or other composition detector can be used, and with greater or lesser staged cooling. A liquid cooled detector could also be utilized in this embodiment provided there is supporting equipment to accommodate the liquid cooling. Another possibility for cooling the detector is by Stirling Engine cooling, however this adds cost and complexity. The MCT composition detectors offer a more compatible electronic biasing consistent with reduced noise than other composition detectors. Other factors considered for single detector selection is the detectivity, commonly expressed in terms of "D*", responsivity to light, the timing of the pulses of light to which the detector is exposed, and the saturation level.

[0050] This embodiment also prefers the economy of a photoconductive type of single detector as opposed to the more expensive photovoltaic detector. While photovoltaic detectors comparably offer less noise in lower pulse frequencies, this is not an issue for this embodiment as it is desirable to stimulate the detector with as high a frequency that the spinning filter wheel illustrated in FIG. 1 item 16, or spinning reflector illustrated in FIG. 5 item 62 will allow.

[0051] Lastly, a detector needs to be selected to respond to light consistent with the range of desired wavelengths. A range of mid-infrared wavelengths for this embodiment can be viewed in **Table 1** which suggests a detector sensitivity range of wavelengths between roughly 3-5 microns. However, if alternative wavelengths are used for such embodiment to measure the gases of interest, the desired range of wavelengths to which the detector is sensitive may have to be adjusted.

[0052] If the range of infrared wavelengths of interest is too broad for a standard detector, a dual substrate detector may be used. A commercially available dual substrate detector contains two different semiconductor compounds, each sensitive to slightly different ranges of wavelengths. They are mounted in a single detector package, one in front of the other so that their active areas nearly coincide. Thus the combination performs as if it were a single detector with sensitivity to a broader range of wavelengths than would otherwise be possible.

[0053] The beam splitter/combiner 44 may comprise any reflective or transmissive device, such as a neutral density filter, which transmit a specified fraction of the incident light and reflect almost all of the rest, treating a broad range of wavelengths equally, or dichroic beam splitter/combiner that can be designed to reflect almost all of the incident light of a specific range of wavelengths, and transmit almost all of the rest. The beam splitter/combiner 44 passes all or portions of visible and/or ultraviolet light 46 so that the visible and ultraviolet spectra may be measured by one or more spectrometers 42, 43. The light which passes through beam splitter/combiner 44 is split off and carried to the respective spectrometers in one of two ways. The first, illustrated in FIG 3, is to focus light onto the end of a Y-shaped optical fiber cable 41 that first receives the light in a single open end of the fiber optic cable, then divides the light within the cable sending a portion of the light to each spectrometer.

[0054] An alternative method of splitting the light to two or more spectrometers, illustrated in FIG. 7, is to use separate beam splitter/combiners 44 and 162 to split light beam 40 twice. Beam splitter/combiner 44 first splits beam 40 into beams 170 and 172. Beam 170 is focused directly into the opening of spectrometer 43 while beam 172 continues on to beam splitter/combiner 162. Beam splitter/combiner 162 then splits beam 172 into beams 174 and 176. Beam 174 is focused on spectrometer 42 while beam 176 continues on to be focused on

the infrared detector 50. In either embodiment, whether cable splitting of light as illustrated in FIG. 3 or multi-beam splitting method of FIG. 11, the light slightly over-bathes the opening to the optical fiber cable (FIG. 3 item 41) or the light orifice of the spectrometer 42,43 for resistance to vibration and coincident reduction of light intensity with the vibration for similar reasons as expressed above for the infrared detector 50.

Table 1: List of Some Example Tailpipe Emissions Channels and their Wavelengths

<u>Component</u>	<u>Wavelength</u>
Carbon Monoxide (CO)	4.65 μ
Carbon Dioxide (CO ₂)	4.30 μ
HC ₁ (Alkane series hydrocarbons)	3.45 μ
Methane (CH ₄)	3.31 μ
HC ₂ (Alkene series hydrocarbons)	3.17 μ
HC ₃ (Alkyne series hydrocarbons)	3.01 μ
H ₂ O _(v)	2.90 μ
Nitrogen Monoxide (NO)	0.226 μ
1,3 Butadiene (C ₄ H ₆)	0.210 μ
Ammonia (NH ₃)	0.208 μ
Reference	3.90 μ

[0055] In a preferred embodiment, the transmission and detection of light at the wavelengths of mid-infrared listed in Table 1 is accomplished by using a spinning filter wheel as the filter component (referred to in FIG. 1 as item 16). FIG. 4 illustrates an exemplary spinning filter wheel. Referring to FIG. 4, the spinning filter wheel contains light filters such as 52 that correspond to wavelengths associated with individual emission components, such as those illustrated in Table 1. One of the filters 54 must correspond with a wavelength at which no gaseous absorption takes place. Such a filter is known as a "reference" filter 54. The light intensity measured from the reference filter 54 is used to normalize the light intensity measured from each of the gaseous filters 52, so that concentrations of those gases may be calculated by a processor (FIG. 6 item 92). FIG. 4 illustrates a wheel having eight filters 52, 54 each utilizing one of the mid-infrared wavelengths of Table 1, however fewer and/or additional filters, corresponding to fewer and/or additional vehicular exhaust constituents, may be used in alternate embodiments. Each filter 52 is designed to allow light of a specific range of wavelengths to pass through it.

[0056] Another innovation regarding the filters 52,54 is that they are quadrants of an industry standard 25 millimeter optical filter. The round, 25 millimeter diameter filters are cut into four pie shapes allowing for filters to cost one-fourth of what they would otherwise cost if an entire industry standard sized filter were to be inserted in each of the open positions on the filter wheel 16. In addition to cost, there is a savings in the amount of rotating mass by quartering the industry standard sized filters that the wheel 16 would have if the filters were installed whole. Lastly, special slots exist in the wheel 16 to allow for a two-piece optical filter 52,54, should this be necessary. There are occasions when a filter manufacturer will supply two filters in order to provide the desired band pass of wavelengths to measure a gas of interest. The wheel 16 has the capability to accept these two-piece filters.

[0057] In addition, the filter wheel preferably will have one or more synchronization marks 56 that may be detected by a synchronization unit 58 to define either the exact filter or the start of a sequence of filters that will be in the optical path. The wheel 16 must have an opaque area 60 between each filter. The opaque areas 60 prohibit source light (FIG. 1 item 10) from getting to a detector when the opaque areas 60 pass in front of the infrared source (FIG. 1 item 10) transforming the incident light beam into a sequence of pulses (FIG. 1 item 17). In operation, the wheel spins about an axis 19 at high speeds, preferably at least 12,000 rotations per minute, to form a sequence of infrared light pulses (FIG. 1 item 17). Faster rotational speeds are even more preferable since they increase the sampling rate of the emission medium. The synchronization unit (FIG. 1 item 65) allows the processor (FIG. 6 item 92) to associate a wavelength of interest, and corresponding gas of interest, with each pulse of light seen by the detector (FIG. 6 item 90). This combination overcomes disadvantages of prior art, which require discrete detectors for each wavelength.

[0058] In accordance with an alternate embodiment of the present invention the light source unit illustrated in FIG. 1 may omit the spinning filter wheel assembly 15,16,19,58. In this embodiment, an alternate detector unit is provided as illustrated in FIG. 5. Incoming light 36 transmitted from the source unit of FIG. 1 and reflected by the reflection unit of FIG. 2 passes through window 35 that has similar characteristics to window of source unit illustrated in FIG. 1, and is reflected by a reflector 38, which directs the light beam 40 onto beam splitter/combiners 44,45 which direct portions 46,47 of the light to the spectrometers 43,42. The rest of the light 61 is focused on spinning reflector 62. Reflector 62 is a single faceted flat mirror with a reflective surface that is optimized for the infrared light wavelengths of interest, such as an enhanced gold reflective surface or other suitable reflective surface. Alternatively, a multifaceted spinning mirror may be used, however the geometry of the rest

of the layout would have to be modified from what is illustrated in FIG. 5. The spinning reflector 62 splays the light in sequence around a stationary array of filters 52,53,54 and gas cells 70 by directing the beam 64 into the side of monolithic ellipsoidal mirror 80 which reflects the light 66 into the array, consistent with the splaying of the light. After passing through each stationary band pass filter 52,53,54 and gas cell 70, the light beam 72 is redirected to and focused on a single infrared detector 50 by a reflector 74 such as a spherical mirror. The reflective surfaces of reflectors 80 and 74 are optimized for the wavelengths of interest in the same way as the surface of spinning reflector 62. The single infrared detector sees a sequence of pulses of light 76 that are essentially the same as those illustrated as FIG. 3 item 48. Each filter 52,53,54 of this array substantially limits the passage of light to a predetermined spectral wavelength or range of wavelengths. Some filter center wave specifications are listed in Table 1. Each gas cell 70 of this array substantially limits the passage of light of a particular spectral pattern of wavelengths absorbed by the known concentration of the gas of interest that the cell 70 contains.

[0059] Another advantage of this embodiment is that there is much less rotating mass in the spinning reflector 62 than in the spinning filter wheel illustrated in FIG. 4. Therefore the spinning reflector 62 can be spun at a much faster rate than the spinning filter wheel illustrated in FIG. 4. Faster spin rate corresponds to a higher sampling rate that can contribute to lower electronic and optical noise levels, and provide better time resolution of a plume of vehicle exhaust constituents.

[0060] It is instructive to refer to the illustration of FIG. 8 to further the understanding on why an ellipsoidal mirror (FIG. 5 item 80) is chosen to distribute light. An ellipsoidal mirror 200 has two focal points or foci 206,208. Such mirrors have the property that all light rays 202 diverging from a small spot near one focal point 206 are reflected in such a way that

those rays 210 are again focused into a small spot near the other focal point 208 of the mirror 200. Given the unique layout of the alternative embodiment of FIG. 5, and commensurate need for a dual foci reflective device for light distribution through a full 360° of rotation of the spinning reflector (FIG. 5 item 62), an ellipsoidal mirror is the best choice for this alternative embodiment.

[0061] An alternative embodiment replaces the monolithic ellipsoidal mirror 80 with individual ellipsoidal mirrors and may place the filters 52,53,54 and gas cell 70 array before the individual ellipsoidal mirrors if layout and construction is simplified. This alternative can provide the advantage of the system suffering less light loss through use of individual mirrors as opposed to the monolithic ellipsoidal mirror 80. The disadvantage is that there may be more adjustments required in order to have the system of FIG. 5 properly aligned such that all light through the system is optimized.

[0062] FIG. 6 illustrates several elements of a computer processing device that may be used in accordance with a preferred embodiment of the present invention. Referring to FIG. 6, the detection unit 90 delivers emissions-related data to a processor 92. The detector may be any of the detectors or spectrometers as illustrated in FIGS. 3 and 5, or any device that receives or contains information collected by such detectors or spectrometers. Such detector systems for the purpose of discussion in FIG. 6 include a means for amplifying and converting the detector signals into digital signals that can pass to the processor 92 via a direct link such as a parallel data bus 94.

[0063] In this embodiment, the detection unit 90 is part of the unit that contains the processor 92, and the delivery is performed over a parallel bus 94 such as that which can be found in AT, ATX, EBX, and other motherboard styles upon which computers are based.

However, the processor 92 and detection unit 90 may be separate, such as with the remote detector 96 illustrated in FIG. 6. Where a remote detector is used, the data may be delivered to the processor 92 by a communications link 100 that delivers the data to an input port 98 such as a communications port. A wireless communications link 102 and receiver 105 for such a wireless communication are also illustrated in FIG. 6. The communications link 102 may be a direct wire, an infrared data port (IrDA), a wireless communications link, global communications network such as the internet, or any other communications medium.

[0064] The system illustrated in FIG. 6 also includes a memory 104 which may be a memory device such as a hard drive, random access memory, or read only memory. A portion of this memory 104 can contain the instructions for the processor 92 to carry out the tasks associated with the measurement of vehicular emissions. Preferably, concentrations of gases may be derived using the Beer-Lambert Law, however other tests and formulae may be used in alternate embodiments.

[0065] The Beer-Lambert Law, as disclosed in other art, relates absorbance of light to a concentration of gas where an amount of change in light intensity at a known wavelength is proportional to the concentration of a gas of interest at the wavelength of light where the gas is absorbed. The Beer-Lambert Law is expressed in terms of transmittance in Equation 1.

Equation 1: Beer-Lambert Law

$$2 - \text{Log}_{10} (\%T) = \epsilon Cl$$

Where:

$\%T$ is the amount of light transmitted through open air and the emissions sample expressed in percent units;

ϵ is the absorption coefficient for the gas of interest at a corresponding wavelength of absorption;

C is the concentration of the gas of interest expressed in parts-per-million (ppm)
 l is the path length expressed in meters.

[0066] Transmittance is further expressed as the amount of light that passes through the gas of interest in proportion to the amount of light that was originally emanated from the light source unit as illustrated in Equation 2.

Equation 2: Transmittance as Expressed in Percent

$$\%T = \frac{I_p}{I_o} \times 100$$

Where:

I_p is amount of light left after passing through the gas sample of interest

I_o is the amount of light that was originally sent through the entire sample path and not absorbed by the gas of interest

[0067] The specific application of Beer-Lambert Law for this embodiment is found in Equation 3. Equation 3 is an algebraic substitution of transmittance “%T” (Equation 2), and subsequent manipulation of Beer-Lambert Law Equation 1 to solve for a concentration of a gas in an open path, as this is the unknown for which this embodiment measures.

Equation 3: Application of Beer-Lambert in this Embodiment

$$C = \frac{2 - \log_{10}\left(\frac{I_p}{I_o} \times 100\right)}{\epsilon \times l}$$

[0068] Other memory devices 106 and 108 such as additional hard disk storage, a CD-ROM, CD-RW, DVD, floppy drive, ZIP® drive, compact flash compatible device such as that which conforms to IBM Microdrive™ specification, or other memory device may also be included. An internal memory device 106 can be used to extend the number of emissions

tests that can be conducted and retained by this preferred embodiment. A removable memory device 108 can be used to make the emissions data portable to allow for the emissions data to be further processed in a centralized location. The device also optionally and preferably includes a display 110 and/or a transmitter 112 for providing output to a user or another device.

[0069] Utilizing a computer processor 92, the intensity measured by the detector unit 90 at a wavelength of interest is compared by the processor 92 to the intensity of light detected by the detector unit 90 at a reference wavelength where no absorption of gases occurs. This method of detection is commonly known as Differential Optical Absorption Spectroscopy (DOAS). This DOAS methodology is a simple, inexpensive means of determining a concentration of a gas of interest emanating from a vehicle tailpipe in open air, and has examples in other art and fields of invention.

[0070] Alternatively, again using a computer processor 92, the intensity measured by a detector unit 90 at a desired wavelength for an interval of time, followed by measuring light at the detector unit 90 for an interval of time at the same desired wavelength with additionally a gas cell of known concentration of gas that absorbs light of the same wavelength can also be used as a methodology to determine a concentration of a gas of interest. This method of detection is commonly known as Gas Filter Correlation Radiometry (GFCr), and is documented in other art. GFCr has the potential to provide improved precision & accuracy of measurements due to the fact that the methodology allows for the constant referencing of a measurement to a known concentration of the gas of interest.

[0071] A preferred embodiment of FIG. 5 shows both DOAS and GFCr methods of determining a concentration of a gas of interest contained within the same embodiment. For

example, an optical filter 53 can be optimized for sampling carbon dioxide (CO_2). Another filter 54 can be optimized to pass wavelengths of light where no absorption of CO_2 or other gases exist; such a filter is used for reference to assess the amount of light that passes through the sample path without CO_2 influence. As the amount of CO_2 concentration increases, the amount of light that the detector 50 observes through filter 53 will decrease, while the amount of light that the detector 50 observes through the reference filter 54 will remain unchanged. This is the fundamental of the DOAS methodology by comparing the amount of light (I_p in Equations 2 and 3) off from the CO_2 filter 53 to the amount of light (I_0 in Equations 2 and 3) from the reference filter 54. Switching the light paths between the CO_2 path, created by filter 53 to detector 50, and reference path, created by reference filter 54 to detector 50, is accomplished by the spinning reflector 62 that plays the light for periods of time between the two mentioned paths and other paths that exist in this embodiment.

[0072] DOAS methodology is also provided in the embodiment illustrated in FIG. 1, however the light path switching is performed by the spinning filter wheel 16 such that, for a moment in time, the filter wheel rotation exposes an optical filter (FIG. 4 item 52) to light (FIG. 1 item 10) for a gas of interest, then for a roughly equal interval of time, the filter wheel exposes a reference filter (FIG. 4 item 54) to the same light (FIG. 1 item 10).

[0073] The GFCr methodology is provided in this embodiment as well. Expanding on the DOAS example above, a CO_2 filter 53 can be paired with another similar characteristic CO_2 filter 52 with the difference that the CO_2 filter 52 has a windowed small cell 70 that contains a sample of CO_2 gas. The amount of gas in the cell 70 is chosen based on the amount of optical depth that is desired with which the non-celled optical path is compared. The CO_2 filter 53 must have balancing windows 78 of the same optical characteristics as the gas cell 70 in order to make the amount of light between both light paths roughly equivalent.

An alternative embodiment to the balancing windows 78 can use a second gas cell 70 in place of the balancing windows 78, but with all air evacuated to a vacuum, or air replaced with nitrogen or other inert gas at partial pressure to provide the optical balance. If a gas is used to fill the balancing cell, the gas cannot have absorption characteristics similar to the gas of interest being measured.

[0074] The balancing windows 78 are added to create an optical balance for the two CO₂ detection paths in the example given, such that the only difference in intensity of light to the detector 50 between the two paths is a change in concentration of the gas of interest. For a period of time, the light travels through the CO₂ filter 52 with CO₂ gas cell 70 and reaches the detector 50. In another time interval of approximately same length, the light will travel through the other CO₂ filter 53 with balancing windows 78 and on to the detector 50. Since the gas cell 70 contains a known concentration and corresponding optical depth of a sample of CO₂, the amount of light in the filter 52 to gas cell 70 to detector 50 path of light exists as a reference to which the amount of light from light path filter 53 to balancing windows 78 to detector 50 is compared. The amount of absorbance from each CO₂ light path is compared to determine a concentration of CO₂ in this example. As with the DOAS method of detection, light path switching is accomplished by the spinning reflector 62 that provides light to each mentioned path for a period of time in addition to making light paths for other gas sampling paths of this embodiment.

[0075] The unique advantage of GFCr is that any interferences to measuring a concentration of CO₂ in this example appear in both CO₂ light paths and therefore is commonly rejected among both light paths. Common mode rejection of interferences does not necessarily happen with the DOAS method of detection of gases, because of the use of a reference filter at a different wavelength, an interference could conceivably absorb light at the

reference wavelength but not at the wavelength corresponding to the gas of interest. Also, the characteristics of the reference filter 54 are different from the other filters 52,53, and create a situation where different filters 52,53,54 pass different wavelengths of light, to which the detector 50 will have greater or lesser sensitivity to such wavelengths. With proper optimizations, these effects may be minimized, but not eliminated.

[0076] It should be noted that it is not necessary to have both DOAS and GFCr methodologies utilized in an embodiment in order to obtain reasonable measurements of concentrations of gases of interest. However it is desirable to have both when economically feasible in order to provide for improved precision and accuracy of measurements. Furthermore, although an example was given here for CO₂, it is possible to utilize GFCr for other gases including but not limited to carbon monoxide (CO), methane (CH₄), and any gas of interest that can be stored over long periods of time in a gas cell without the reference gas of interest degrading, attacking the walls of the cell and compromising the sample, or the reference gas combining with contaminants within the cell causing the reference concentration to no longer be known. GFCr methodology also is beneficial for speciation of hydrocarbons, as the gas cell 70 can be utilized as a sort of notch filter to indicate a particular gas of interest from a group of gases such as hydrocarbons.

[0077] Referring back to FIG. 6 the processor 92 of the embodiment, coupled with the appropriate instruction set contained within memory 104, can be capable of conducting either DOAS, GFCr, or simultaneously both methodologies of detection of concentrations of gases and then applying the concentrations to a combustion equation. Previous art in this field of invention has documented combustion equations that utilize ratioing concentrations of gases of interest relative to carbon dioxide (CO₂) to correct for any dilution effects in the exhaust stream of the vehicle being tested. The memory 104 can contain combustion equations

unique to different fuels used to power vehicles that are tested by this preferred embodiment. Determination of the type of fuel used to power a tested vehicle can be done in the processor 92 at the time of measurement of the tailpipe emissions, or after emissions testing activities have concluded at the monitoring site in a centralized data processing facility. A method for determining the type of fuel of a vehicle is disclosed in U.S. Patent application serial number 09/928,720 entitled "METHOD AND SYSTEM FOR DETERMINING THE TYPE OF FUEL USED TO POWER A VEHICLE", filed August 13, 2001, the disclosure of which is hereby incorporated by reference in its entirety.

[0078] FIG. 9 illustrates a preferred embodiment including a light source 120 capable of emitting at least one beam of light 122 having known emission intensities corresponding to one or more of infrared, visible, and ultraviolet spectra. The system also includes a reflection unit 124, a detection unit 90 capable of receiving the beam and measuring received intensities corresponding to the light spectra, and a processor 92 capable of comparing received intensities and identifying a concentration of a gas of interest. The light 122 is transmitted through a gas, such as air containing vehicle emissions, reflected, then detected for analysis and measurement of the amount of absorption that has occurred at known wavelengths. The amount of absorption may be used to determine concentrations of gases corresponding to the specific wavelengths.

[0079] Preferably, as illustrated in FIG. 10, the system also includes a first reflector 130 positioned to receive the beam 128 from the light source 120 and reflect the beam 132 toward the reflection unit 124. The reflection unit 124 is positioned to receive the beam 132 from the first reflector 130 and reflect the beam 134 toward a second reflector 136. Also preferably, the second reflector 136 is positioned to receive the beam 134 reflected by the reflection unit 124 and reflect the beam 138 toward the detection unit 90. In a preferred

embodiment, each reflector 130,136 comprises an off-axis paraboloidal mirror, however a spherical or other similar mirror could be used.

[0080] Referring to FIG. 11, a paraboloidal mirror 180 has the property that light rays 182 emitted from and diverging from a small spot of a light source 184 placed near the paraboloidal mirror 180 focus 186 are reflected into a beam of rays 188 nearly parallel to the axis of rotation 190 of the mirror.

[0081] Conversely, as illustrated in FIG. 12, a beam of light rays 192 traveling nearly parallel to the axis of rotation 190 of a paraboloidal mirror 180 become rays 194 reflected toward and concentrated into a small spot near the paraboloidal mirror focus 186. The significance of a light beam of nearly parallel rays 192 is that the intensity of the light beam changes very little over a great distance, a desirable trait for long path, open-path gas detection systems. Off-axis paraboloidal mirrors have the advantage that the light source or detection unit may be located to the side of the reflected beam instead of in its midst. This means that the full diameter of the mirror can be used for the optical measurements. Layout of the source and detector components is also simplified. Spherical mirrors are more "fuzzy" at the focus, and incoming/outgoing light rays are not nearly as parallel as with the parallel rays 192 of the paraboloidal mirror 180. Light rays that do not travel in the parallel path are lost from the optical path and as a consequence, are part of the reduced efficiency of an optical system that utilizes spherical mirrors. Nonetheless, other factors such as availability of product, production cost, etc. all factor in the decision whether to use the preferred paraboloidal mirror 180 for sending/receiving light in the embodiment, or utilize spherical mirrors in their place.

[0082] Returning to FIG. 10, a beam of light travels along an optical path 128, 132, 134, and 138 from the light source 120, to the first reflector 130, to the reflection unit 124, to the second reflector 136, to the detection unit 90. In this embodiment, the system also includes, as seen in FIG. 13, one or more additional light sources 144,146, each capable of emitting a beam of light 148, 152 having known emission intensities corresponding to one or more of infrared, visible, and ultraviolet spectra, as well as one or more beam splitter/combiners 140,142, if necessary, positioned to direct beams 148,152 from the additional light sources 144,146 along essentially the same optical path 154, 132, 134, and 138 as illustrated in FIG. 10. The beam splitter/combiners 140,142 may be neutral density filters, or alternatively they may be wavelength sensitive beam splitter/combiners, such as dichroic beam splitter/combiners.

[0083] In another embodiment, illustrated by FIG. 14, the light sources 10,12, beam splitter/combiners 140,160, infrared detector 50, and spectrometer 43 are positioned so that ultraviolet light beam 212 from source 12 is traveling along essentially the same optical path, but in the opposite direction from infrared light beam 14 from source 10. This innovation is referred to herein as "opposed sources". An embodiment using opposed sources may eliminate the need for additional expensive, light attenuating components. For instance, if ultraviolet light 212 is directed towards, instead of away from, the infrared detector 50, the signal from the infrared detector 50 can degrade. If light 212 from an ultraviolet source 12 is traveling in the opposite direction from the light 14 emanating from the infrared source 10, the ultraviolet light 212 is naturally kept away from the infrared detector 50 without the use of additional wavelength dependent filters or beam splitter/combiners. Light sources 12,10 and detectors 43, 50 need to be matched with optical components of corresponding F-numbers for efficient light transmission. An embodiment using opposed sources, and first and

second reflectors 130,136 of significantly different F-number, allows the sources or detectors requiring a higher F-number to be matched with the reflector with the higher F-number, and the sources and detectors requiring a lower F-number to be matched with the reflector with the lower F-number. This eliminates the need for additional optical components for F-number matching. Finally, opposed sources may significantly simplify component layout and reduction of thermal and electrical interference among components.

[0084] FIG. 13 shows one possible arrangement of three sources 120, 144 and 146. In one preferred configuration, the source 120 is an infrared source, the source 144 is a visible light source, and source 146 is an ultraviolet light source. In this example, ultraviolet light reflects off splitter/combiner 142 but does not pass through any splitter/combiners. The infrared light passes through two splitter/combiners. However, the arrangement of these sources may be interchanged in any combination, and one or more source types may be omitted entirely.

[0085] FIG. 14 depicts an ultraviolet source 12 and an infrared source 10. The ultraviolet source 12 could also be combined with a visible light source in a manner similar to the combination shown in FIG. 1, either using a pass through ultraviolet source or by providing an additional splitter/combiner to combine the ultraviolet and visible light.

[0086] Thus, the many features and advantages of the invention are apparent from the detailed specification, and thus, it is intended by the appended claims to cover all such features and advantages of the invention which fall within the true spirit and scope of the invention. Further, since numerous modifications and variations will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation

illustrated and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220